

Product Datasheet

PAVO ROUND



Linear Pendant Luminaire



Description:

Suitable for suspended or surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation	: Surface / Suspended	Kelvin	: 3000-4000-6000
Warranty	: 5 years	CRI	: >80
Lamp Type	: LED	LED Lifetime	: 50.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Difusser	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:




Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
PLRG1	28	Pavo Lineer Surface Gear 1	3360	55-85-Ø300
PLRG2	60	Pavo Lineer Surface Gear 2	7200	55-85-Ø500
PLRG3	88	Pavo Lineer Surface Gear 3	10560	55-85-Ø800
PLRG4	128	Pavo Lineer Surface Gear 4	15360	55-85-Ø1100

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colours



Quality Certificiate:

