

Product Datasheet



REG

Triproof Luminaire


Description:


Suitable for surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

| Installation | : Surface | Kelvin | : 3000-4000-5000-6500 |
|--------------|-----------|--------------|-----------------------|
| Warranty | : 5 years | CRI | : >90 |
| Lamp Type | : LED | LED Lifetime | : 80.000 h |
| Housing | : Alm | Power Supply | : 110-240V 50-60Hz |
| Glass | : PC | Op. Temp. | : -20°C / +45 °C |
| IP | : 65 | IK Factor | : IK08 |

Prometrical Data:





Technical Details:

| Item | Power (W) | Description | Light Output (Lm) | Dimensions (mm) |
|-------|-----------|-----------------------|-------------------|-----------------|
| REGG1 | 18 | Reg Waterproof Gear 1 | 1764 | 600-90-75 |
| REGG2 | 25 | Reg Waterproof Gear 2 | 2450 | 1200-90-75 |
| REGG3 | 38 | Reg Waterproof Gear 3 | 3724 | 1200-90-75 |
| REGG4 | 60 | Reg Waterproof Gear 4 | 5880 | 1500-90-76 |

Technical Options:

*Dali

*Dimmer

*Emergency Kits

Quality Certificiate:



- Tel : +90 (212) 798 3041 42
- Fax : +90 (212) 798 3043

Web : <u>www.entekled.com.tr</u>

ENTEK LED reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.