

# VENUS

## COB Downlight Luminaire



C

а


## Description:


Suitable for recessed mounting in unventilated or ventilated ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

### **Technical Features:**

: Recessed	Kelvin	: 3000-4000-6000
: 5 years	CRI	: >90
: COB LED	LED Lifetime	: 80.000 h
: Aluminium	Power Supply	: 110-240V 50-60Hz
: Reflector	Op. Temp.	: -20°C / +45 °C
: 20		
	: 5 years : COB LED : Aluminium : Reflector	: 5 years CRI   : COB LED LED Lifetime   : Aluminium Power Supply   : Reflector Op. Temp.

### Prometrical Data:





## Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
VCG1	10	Venus 2" COB Downlight Gear 1	1100	Q117-103-Q105
VCG2	15	Venus 3" COB Downlight Gear 2	1650	Q147-103-Q130
VCG3	20	Venus 4" COB Downlight Gear 3	2200	Q173-103-Q158
VCG4	24	Venus 5" COB Downlight Gear 4	2640	Q192-103-Q175
VCG5	28	Venus 6" COB Downlight Gear 5	3080	Q229-110-Q220

### **Technical Options:**

\*Dali

### \*Dimmer

\*Emergency Kits

#### Quality Certificiate:



Tel	: +90 (212) 798 3	3041 - 42
Fax	: +90 (212) 798 3	3043

ENTEK LED reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.

Web : www.entekled.com.tr