


HOUSTEN RIM



Floodlight Luminaire



Description:

Suitable for surface mounting on somewhere. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Warranty	: 5 years	Kelvin	: 3000-4000-5000-6500
Lamp Type	: LED	CRI	: <90
Housing	: Aluminium	LED Lifetime	: 80.000 h
Optics	: Lens	Power Supply	: 110-240V 50-60Hz
Glass	: Tempered Glass	Op. Temp.	: -30°C / +50 °C
IP	: 66	Number Of LED	: 24

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
RFG1	30	Houston Rim Gear 1	4200	394-240-100
RFG2	50	Houston Rim Gear 2	6150	394-240-100
RFG3	60	Houston Rim Gear 3	7250	394-240-100
RFG4	75	Houston Rim Gear 4	8900	394-240-100
RFG5	90	Houston Rim Gear 5	11250	394-240-100
RFG6	100	Houston Rim Gear 6	13500	394-240-100

Technical Options:

*Dali

*Dimmer

Quality Certificate:



Tel : +90 (212) 798 3041 - 42

Fax : +90 (212) 798 3043

Web : www.entekled.com.tr

ENTEK LED reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes.