

TATA SURFACE



Downlight Luminaire



Description:

Suitable for surface mounting on ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.

Technical Features:

Installation	: Surface	Kelvin	: 3000-4000-6000
Warranty	: 3 years	CRI	: >90
Lamp Type	: LED	LED Lifetime	: 80.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Difusser	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
TDG1	7	Tata 2" Downlight Gear 1	700	Q100-150
TDG2	10	Tata 3" Downlight Gear 2	875	Q100-150
TDG3	16	Tata 4" Downlight Gear 3	1486	Q126-150
TDG4	18	Tata 5" Downlight Gear 4	1897	Q150-150
TDG5	20	Tata 6" Downlight Gear 5	2107	Q150-150

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colours



Quality Certificate:

