


ELA

Downlight Luminaire

Description:



LED Downlights each offer different benefits from the beam distribution, trim selection and installation methods. Whether you are installing them in a new construction or in a retrofit application, they will fit seamlessly into your lighting application.



Technical Features:

Installation	: Recessed	Kelvin	: 3000-4000-6000
Warranty	: 5 years	CRI	: >90
Lamp Type	: LED	LED Lifetime	: 80.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Difusser	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
EDG1	6	Ela 1" Downlight	750	Q80-55-Q70
EDG2	8	Ela 2" Downlight	1000	Q10-55-Q85
EDG3	10	Ela 3" Downlight	1250	Q117-55-Q105
EDG4	15	Ela 4" Downlight	1875	Q147-55-Q130
EDG5	20	Ela 5" Downlight	2500	Q173-50-Q158
EDG6	23	Ela 6" Downlight	2875	Q190-55-Q175
EDG8	26	Ela 8" Downlight	3250	Q231-55-Q214

Technical Options:

*Dali

*Emergency Kits

*Dimmer

Colours

White Black Chrome Golden



Quality Certificate:

