


SLOT

Downlight Luminaire

Description:



Suitable for recessed mounting in unventilated or ventilated ceilings. The luminaire must not be covered with insulation. For further details please contact with us. Light sources are fitted in the luminaire. The luminaire offer energy performance and much longer lifetime. The Luminaire will be accurate and realistic solution for you.



Technical Features:

Installation	: Recessed	Kelvin	: 3000-4000-6000
Warranty	: 5 years	CRI	: >90
Lamp Type	: LED	LED Lifetime	: 80.000 h
Housing	: Aluminium	Power Supply	: 110-240V 50-60Hz
Glass	: Difuser	Op. Temp.	: -20°C / +45 °C
IP	: 20		

Prometrical Data:



Technical Details:

Item	Power (W)	Description	Light Output (Lm)	Dimensions (mm)
SDG1	6	Slot Downlight Gear 1	750	Q95-65-Q85
SDG2	8	Slot Downlight Gear 2	1000	Q117-70-Q105
SDG3	10	Slot Downlight Gear 3	1250	Q147-75-Q130
SDG4	15	Slot Downlight Gear 4	1875	Q173-75-Q158
SDG5	18	Slot Downlight Gear 5	2250	Q190-85-Q175
SDG6	23	Slot Downlight Gear 6	2875	Q229-90-Q214

Technical Options:

- *Dali
- *Dimmer
- *Emergency Kits

Colours



Quality Certificate:

